HOMELIFT Low Speed Elevator

EXAMPLES OF USE:




















Authorized Representative:

The alliance between comfort and design that covers the essential need and improves the value of your building. Conceived to be installed at existing buildings and to remove architectural barriers.





ELESEI Fabricación de elevadores y montaca

Ctra. Sevilla - Mairena del Alcor, km. 0,8 41500 Alcalá de Guadaíra, Seville, Spain

Ph. +34 **955 634 649**

email: eleser@eleser.es www.eleser.es/en/ We Improve your Quality of Life with All Security



HOMELIFT Low Speed Elevator

It is the solution to improve the quality of life at home, at small public buildings, or at reduced size residents associations.

Especially performed for elderly and people with reduced mobility.

MAIN ADVANTAGES:

- Comfortable
- Quick and easy to install
- Low electricity consumption
- Maximum security
- Particular facilities for elderly and other people with reduced mobility
- Minimum pit of 200mm ≈7.7in

USEFUL FOR:

- Terraced villas
- Points of sales
- Small hotels and restaurants
- Nursing homes
- Public buildings

OPTIONS:

- Cabin colour swatch
- Range of flooring types
- Half mirror or full-height vertical mirror
- Floor indicator display in cabin (standard for lifts with cabin doors)
- Cabinet for power unit and control board

SAFETY:

- Light curtain in the cabin
- Possibility of cabin automatic doors

Option for built-in lift telephone

- Telephone in the interior of the cabin
- Stainless steel operating push-button containing: Alarm; Excess load indicator; Emergency light; Users restriction key; Emergency stop switch in cabin's operating
- panels, or door open for lifts with cabin door • Automatic rescue device in case of failure at the electrical supply
- Approved fire-resistant doors
- Immediate mechanical wedging following a suspected break or slackening of the suspension cables
- Non-slip flooring

TECHNICAL FEATURES:

- Load capacity: from 180kg ≈397lbs 2 person, until 450kg ≈992lbs - 6 person
- Usable surface: from 700x700mm ≈27.5in, until 1400mm ≈55in x 1200mm≈47in
- Maximum travel: 15 000 mm ≈590in
- Speed: until 150mm ≈5.9in per second
- Smooth and silent hydraulic power unit
- Motor Power: 2.2 KW or 2.9 KW
- Electricity Supply:
 - One Phase 230 Vac
 - Three phase 230/400 Vac
- Operating buttons with light indicators and Braille
- Hold-to-run operation (lift with light curtains), or automatic operation (lift with automatic doors)
- Pre-assembled electrical installation



LANDING DOORS




CABIN WALLS



Hinged Solid







Skinplate

Peach

Special preparation for stone floors or other, please ask us.





(flat bus type)

Skinplate

Cream

CABIN DOORS





Stainless Steel and/or glass wall

FLOORING

Skinplate Light Wood



Pearl Rubber



Sand Rubber

Skinplate Dark Wood



Anthracite Rubber

Skinplate

Blue Marine





Skinplate

Blue Sky





DETAILS:













DIRECTIVE & STANDARDS:

This product has been manufactured according to Machinery Directive 2006/42/EC.

The following Standards & Rules have been considered for its design and manufacture:

UNE-EN ISO 12100:2012 UNE-EN 81-20:2017

NOTIFIED CONTROL BODY



www.imq.it/en

