

Goods Only Lifts

We improve your Productivity

PHE-2PHE Goods Lifts

Main Advantages

- Minimum maintenance.
- Excellent value for money.
- Ecological, reduced energy consumption.
- Very safe, has a parachute valve.
- Different models, allowing us to offer a product that is best suited to the client's needs.
- Total accessibility from all sides.
- High resistance.
- Technology determining the development of the product.
- Safe and reliable hydraulic unit.
- · Design which allows easier loading and unloading.

General Features

Designed to meet the needs of vertical goods transportation with hydraulic drive.

- Hydraulically operated lifting platform, specifically designed for lifting goods.
- Installation within a closed shaft with resistant walls, enclosure manufactured from building materials or metal.
- As protective and safety measures, all entrances must have an access door with electric and mechanical safety locking device.
- Automatic relevelling (optional), the platform's floor remains constantly levelled when loading and unloading.
- Non-slip flooring.
- Barriers to secure the load. The barriers surround the entire perimeter of the goods lift, except for the goods entrance. ELESER provides options adapted to specific company's needs.

Technical Features

- Hydraulic elevation by single-acting pistons, with a 2:1 or 4:1 force ratio.
- Automatic manoeuvre: 24Vcc.
- Motors: 230 / 400 Vac three-phase & 230 Vac single-phase.



One column Goods Lift

- Platform with rated loads from 150kg to 3,000kg.
- Only one column.
- Up to three entrances.
- Non-slip surface.

Standards and Regulations:

This product is manufactured according to european regulation:

- Directive 2006/42/€C

The following standards and specifications have been considered for the design and manufacture:

- Standard UNE-EN ISO 12100-1292-1
- Standard UNE-EN ISO 12100-1992-2
- Standard UNE-EN 81-2:2001
- REBT: Low Voltage Electrotechnical Regulation









Double column Goods Lift

- Platform with rated loads from 1,000kg to 3,000kg.
- Two lateral columns.
- Up to three entrances.
- Non-slip surface.



Double opposite column Goods Lift

- Platform with rated loads from 1,000kg to 6,000kg.
- The columns are face to face.
- Up to two entrances.
- Non-slip surface.

